



Submittal Data Sheet

06-Ton VRV-WIII Heat Pump Unit

RWEYQ72PYDN

FEATURES

- Compact lightweight casing (Height: 39-3/8", Weight: 330 lbs.) allows flexibility in system layout and installation
- Modular - can be installed in double-decker style if needed
- Larger single system capacity ensures wider application range for satisfying floor-by-floor loads of commercial buildings
- Modular and flexible - 7 combinations of condensing unit, up to 21-ton serving up to 32 indoor units
- Continuous operation allows for cold climate capability delivering comfortable heating performance with no defrost
- Operates with closed loop cooling tower, dry cooler, boiler, and geothermal solutions for optimum flexibility in system layout
- Standard Limited Warranty: 10-year warranty on compressor and all parts

BENEFITS

- Connects to the full suite of advanced Daikin Control Solutions including I-Touch Controller and I-Touch Manager for complete system control
- BMS flexibility with integration capabilities to Open Protocol Building Management Systems via the Daikin BACnet® and LonWorks® interfaces
- Flexible piping layout - up to 980 feet of pipe (390 feet max. linear liquid piping length) and 164 feet height difference
- Maximum system diversity with up to 130% connectivity of nominal capacity
- Flexibility with optimum water flow rates per module of 16 gpm or greater (operable range 13.2 ~ 39.5 gpm).
- The advanced, self-diagnostic, auto-check function will detect a malfunction and immediately display the type and location so it can be resolved quickly and effectively.



VRV-WIII

AIR CONDITIONING
CERTIFIED
www.airexchange.com





Submittal Data Sheet

06-Ton VRV-WIII Heat Pump Unit

RWEYQ72PYDN

PERFORMANCE

Outdoor Unit Model No.	RWEYQ72PYDN	Outdoor Unit Name:	06-Ton VRV-WIII Heat Pump Unit
Type:	Heat Pump	Unit Combination:	
Rated Cooling Capacity (Btu/hr):	69,000	Rated Cooling Conditions:	Indoor (°F DB/WB): 81 / 66 Ambient (°F DB/WB): 95 / 75
Nom Cooling Capacity (Btu/hr):		Rated Heating Conditions:	Indoor (°F DB/WB): 68 / 68 Ambient (°F DB/WB): 47 / 43
Cooling Input Power (kW):	4.20	Rated Piping Length(ft):	
Rated Heating Capacity (Btu/hr):	77,000	Rated Height Difference (ft):	0.00
Heating Input Power (kW):	4.00	IEER (Non-Ducted/Ducted):	24.10 / 24.10
Nom Heating Capacity (Btu/hr):		Heating COP 17F (Non-Ducted/Ducted):	/
		Heating COP (Non-Ducted/Ducted):	4.9 / 4.9

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	460 / 60 / 3	Compressor Type	Inverter
Power Supply Connections:	L1, L2, L3 Ground	Gas Pipe Connection (in):	3/4
Min. Circuit Amps MCA (A):	10.20	Liquid Pipe Connection (in):	3/8
Max Overcurrent Protection (MOP) (A):	15.00	H/L Pressure Connection (in):	
Max Starting Current MSC(A):		H/L Equalizing Connection (in):	
Rated Load Amps RLA(A):	5.3	Water Inlet Connection (in):	1-1/4
Dimensions (HxWxD) (in):	39-3/8 x 30-3/4 x 21-11/16	Water Outlet Connection (in):	1-1/4
Net Weight (lb):	343	Condensate Drain Outlet (in):	1/2
Capacity Control Range (%):	23 - 100	Sound Pressure (H) (dBA):	50
Capacity Index Limit (Btu/hr):	36 - 94	Sound Power Level (dBA):	
Unit Heat Rejection (kW):	0.64	Max. No. of Indoor Units:	12

